

## Features

- Retrofit Kits available in 75W and 400W (other power outputs are available by special order)
- Replaces +400W and +1000W traditional Metal Halides
- Mean Well Drivers
- Kit can be installed in enclosed fixtures without the risk of heat damage to the LED light component
- Rated lifespan of over 70,000 hours
- Kits available in 5,000°K CCT
- Operating Voltage : 200W (100-277 VAC) / 400W (200-480 VAC)
- Operating Temperature: -22°F to 122°F
- Power Supply Efficiency: >95%
- CRI (ra): >80 / Beam Angle: 120°
- Lens type: Clear
- UL and DLC rated
- 75W: 4.0A (100-240 VAC) & 300W: 1.2A (100-277 VAC)400W:0.88A (200-480 VAC)
- IP64 Rated
- Die Cast Aluminum
- 5 Year limited warranty



## Performance Summary & Description

MODEL	POWER	LUMENS	Efficacy	INPUT VOLTAGE	FREQUENCY	CCT	ETL	Base	FCC
SRK-75	75W	7,500LM	100Lm/w	100-277VAC 347-480VAC Option	50-60Hz	3000-5000K	✓	E26/39	✓
SRK-120	120W	12,000LM	100Lm/w	100-277VAC 347-480VAC Option	50-60Hz	3000-5000K	✓	E26/39	✓
SRK-300	300W	30,000LM	100Lm/w	100-277VAC 347-480VAC Option	50-60Hz	3000-5000K	✓	E26/39	✓
SRK-400	400W	40,000LM	100Lm/w	100-277VAC 347-480VAC Option	50-60Hz	3000-5000K	✓	E26/39	✓