

Rocker Switch

Single - ENSW1 / Double - ENSW2



Self-powered wireless controls are simple to install.

Entuit Single and Double Rocker Pads use radio frequency technology to communicate wirelessly with other Entuit devices and provide convenient control of lighting, temperature and miscellaneous electric loads. The rocker pads are self-powered and never require batteries because the simple act of pressing the rocker generates enough energy to send a signal to other Entuit devices. Use them in conjunction with Entuit sensors and controls to maximize efficiency and provide a level of comfort and convenience you cannot achieve with traditional switches. Entuit products feature clean contemporary styling, making them an attractive addition that's sure to compliment any décor.

Features & Benefits

- Communicates wirelessly with other Entuit devices using EnOcean radio frequency technology.
- Wireless - no additional wire to run so installation is fast and easy. Install them where you want them and then move them anytime.
- Self-powered - no batteries to replace and no on-going maintenance.
- Decorator style rocker pads capable of performing switching and dimming functions.

SPECIFICATIONS

| | |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Supply | Electrodynamic harvesting |
| Inputs / Outputs | <ul style="list-style-type: none">• 1 or 2 button rocker switch options• Radio Frequency (RF) transmitter |
| Communications | 902 MHz EnOcean RF transmitter |
| Transmission Range | 80 ft. (25m) |
| RF Transmission | On press and release of rocker button |
| Dimensions | Single: 3.8" H x 3.4" W x .85" D Double: 3.8" H x 3.5" W x .85" D |
| Weight | Single: 3.5oz. |
| Mounting | Surface mounted on wall (using included mounting screws) Can also be flush mounted by optional use of electrical wall box or low-voltage ring |
| Environment | <ul style="list-style-type: none">• Indoor use only• 32° to 131° F (0° to 55° C)• 5% to 95% relative humidity (non-condensing) |
| Agency Listing | FCC, I.C. |